



Emergency Contact: Chemtrec (800) 424-9300
Or Norco (208) 336-1643

1125 West Amity Road
Boise, ID 83705
(208) 336-1643

Sulfur Dioxide 0.0001% to 1% in Nitrogen

MATERIAL SAFETY DATA SHEET

Identification

Product Name: Sulfur Dioxide 0.0001% to 1% in Nitrogen
CAS Number: N/A
Chemical Family: Gas Mixture
Chemical Formula: SO₂ in Nitrogen
Synonyms: N/A
MSDS Identification Code/Number NLB 2200
Prepared By: Quality Dept.

Revision Date: 08/18/10
Last Review Date: 08/21/13

Composition, Information on Ingredients

Exposure Limits¹:

INGREDIENT	% VOLUME	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Sulfur Dioxide Formula: SO ₂ in N ₂ CAS: 7446-09-5 RTECS#: WS4550000	≤ 1%	5 ppm TWA	2 ppm TWA 5ppm STEL	LC50: 2520 ppm Inhalation/rat (1 hr.)
Nitrogen Formula: N ₂ CAS: 7727-37-9 RTECS#: QW9700000	99.0 to 99.9999%	None Established	Simple Asphyxiant	Not Available

¹ Refer to individual state or provincial regulations, as applicable, for limits that may be more stringent than those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993).

³ As stated in the ACGIH 2007 Threshold Limit Values for Chemical Substances and Physical Agents.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.
IDLH: 100 ppm (SO₂)

Hazards Identification

Emergency Overview:

Colorless non-flammable gas with characteristic odor. May cause skin, eye and upper respiratory irritation. High concentrations of sulfur dioxide may cause pulmonary edema and chemical pneumonitis. Nitrogen acts as a simple asphyxiant by displacing oxygen necessary to support life. Sulfur dioxide reacts with water to produce sulfuric acid. Contents under pressure. Use and store below 125° F (52° C).

Route of Entry:

Skin Contact Yes	Skin Absorption No	Eye Contact Yes	Inhalation Yes	Ingestion No
---------------------	-----------------------	--------------------	-------------------	-----------------

Hazards Identification continued

Health Effects:

Exposure Limits Yes	Irritant Yes	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects Sulfur dioxide may act as a cocarcinogen with benzo[a]pyrene in the rodent respiratory tract.		

Carcinogenicity: NTP: No IARC: No OSHA: No

Eye Effects:

May cause irritation with associated redness, swelling, and tears. Contact with rapidly expanding gas near the point of release may cause frostbite.

Skin Effects:

May irritate the skin upon contact.. Contact with rapidly expanding gas near the point of release may cause frostbite with redness, skin color change to gray or white, and blistering.

Ingestion Effects:

Ingestion is unlikely. Product is a gas at room temperature.

Inhalation Effects:

Sulfur dioxide is very irritating and generally causes sever nose, throat and respiratory irritation before toxic concentrations are present. Exposure to low concentrations of sulfur dioxide may cause sneezing, coughing, bronchospasm, and systemic acidosis. Relative high concentrations of product would have to be inhaled for pulmonary edema or respiratory arrest to occur, however, individual susceptibility to the effects of sulfur dioxide varies.

Prolonged or repeated low level exposures may impair lung function and cause corrosion of the teeth.

Reproductive toxicity and developmental changes in newborn have been observed in experimental animals exposed to sulfur dioxide. Sulfur dioxide is mutagenic in experimental cell assay systems.

Nitrogen acts as a simple asphyxiant. Accumulation of high concentrations can displace oxygen content in the air necessary to support life.

Medical Conditions Aggravated by Exposure:

May aggravate pre-existing eye, skin and respiratory disorders. Persons with pre-existing respiratory, nasal and cardiovascular disease may be more susceptible to effects of sulfur dioxide exposure.

NFPA Hazard Codes

Health: 1
Flammability: 0
Instability: 0

HMIS Hazard Codes

Health: 1
Flammability: 0
Physical Hazard: 3

Ratings System

0 = No Hazard
1 = Slight hazard
2 = Moderate Hazard
3 = Serious Hazard
4 = Severe Hazard

Hazard ratings were assigned according to Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, *CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition*.

First Aid Measures

Eye:

PERSONS WITH POTENTIAL EXPOSURE TO SULFUR DIOXIDE SHOULD NOT WEAR CONTACT LENSES. Flush eyes with large amounts of water for at least 15 minutes, holding eyelids open to ensure adequate rinsing. If irritation persists or frostbite is suspected, seek immediate medical attention.

First Aid Measures Continued

Skin:

Remove contaminated clothing and flush affected area with large quantities of water. For frostbite, seek medical attention immediately; do NOT rub the affected areas or flush them with water. In order to prevent further tissue damage, do NOT attempt to remove frozen clothing from frostbitten areas.

Ingestion:

Not anticipated; product is a gas at room temperature.

Inhalation:

PROMPT REMOVAL FROM THE CONTAMINATED AREA AND IMMEDIATE MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.

Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep victim warm and calm. Further treatment should be symptomatic and supportive. Seek immediate medical attention.

Fire Fighting Measures

Conditions of Flammability: Not flammable		
Flash point: Gas	Method: Not Applicable	Autoignition Temperature: None
LEL (%): Not Applicable	UEL (%): Not Applicable	
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

Fire and Explosion Hazards:

Nonflammable. Cylinders may vent rapidly or rupture violently from pressure when involved in a fire situation.

Extinguishing Media:

Use media suitable for surrounding combustible or flammable materials. Sulfur dioxide forms sulfuric acid solutions with water.

Fire Fighting Instructions:

Stop the flow of gas if it can be done without risk. Use water spray to cool surrounding containers. Continue to cool surrounding containers until well after flames are extinguished. Firefighters should wear a full-face piece, NIOSH/MSHA-approved self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout gear.

Accidental Release Measures

Isolate hazard area, evacuate personnel and deny entry to unauthorized/unprotected individuals. Extinguish all ignition sources and ventilate closed spaces and low areas. Personnel entering area should wear appropriate protective equipment, including respiratory protection suitable for unknown concentrations. Personnel should not re-enter an area until sulfur dioxide has sufficiently dispersed and adequate oxygen re-established. If a leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. If leak is in container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest Norco/NorLab location.

Handling and Storage

Electrical classification:

Non-hazardous

Use only in well-ventilated areas. Valve protection caps must remain in place on refillable cylinders unless cylinder is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the

Handling and Storage Continued

discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non-combustible construction away from heavy traffic areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125^oF (52^oC). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time.

For additional recommendations, consult Compressed Gas Association Pamphlets P-1.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

Exposure Controls, Personal Protection

Engineering Controls:

Use a laboratory hood with forced ventilation for handling small quantities. Use local exhaust to prevent accumulation above the exposure limit.

Eye/Face Protection:

Chemical safety goggles with full face shield.

Skin Protection:

Protective gloves as appropriate for the job (SaranexTM, BarricadeTM and responderTM are appropriate for greater than 8 hour exposures to pure sulfur dioxide).

Respiratory Protection:

A NIOSH/MSHA-approved full-facepiece SCBA operated in positive mode and/or any supplied air respirator with a full-facepiece and operated in a positive pressure mode in combination with an auxiliary self contained breathing apparatus operated in positive pressure mode should be used for high or unknown concentrations. Respirators should be stored in an area not likely to be contaminated.

Other/General Protection:

Safety shoes, safety showers and an emergency eyewash station should be available.

Physical and Chemical Properties

PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Not available	
Vapor density (Air = 1)	: 0.97	
Evaporation point	: Not available	
Boiling point	: -320.4	^o F
	: -195.8	^o C
Freezing point	: -345.9	^o F
	: -209.9	^o C
pH	: Not available	
Specific gravity	: Not available	
Oil/water partition coefficient	: Not available	
Solubility (H ₂ O)	: ≤ 1% (mixture)	
Odor threshold	: No data	
Odor and appearance	: Colorless gas/vapor with a highly irritating, pungent odor.	

Stability and Reactivity

Stability:

Stable under normal conditions.

Incompatible Materials:

Mixture contains only 0-1% sulfur dioxide. The following data is for pure sulfur dioxide. Reacts violently with peroxides, chromates, permanganates and oxygen difluoride. It also reacts with chlorates to form chlorine, which may become explosive at elevated temperatures. Forms sulfuric acid solutions with water.

Hazardous Decomposition Products:

Sulfur dioxide reacts with water to form sulfuric acid. Thermal decomposition produces toxic CO_x and SO_x.

Hazardous Polymerization:

Will not occur.

Toxicological Information

Inhalation:

Dryness of the nose and throat and bronchoconstriction occurs following inhalation of 5 ppm or more sulfur dioxide. From 6 to 8 ppm a decrease in tidal respiratory volume occurs. Exposure to 20 ppm sulfur dioxide caused bronchospasm and 50 ppm causes extreme discomfort.

Skin and Eye:

Sulfur dioxide is an irritant at 8 to 12 ppm with conjunctival irritation and lacrimation. Irritation becomes severe at 50 ppm.

Sub chronic:

Repeated exposure to sulfur dioxide has caused thickening of the mucous layer in the trachea and increases in goblet cells and mucous glands in test animals.

Chronic:

No evidence of decreased pulmonary function was seen in guinea pigs exposed to 5 ppm sulfur dioxide for 1 year and monkeys exposed to 1.3 ppm for 78 weeks. Decreased lung compliance and decreased pulmonary flow-resistance was seen in dogs exposed continuously to 5 ppm for 225 days.

Although there is no evidence that sulfur dioxide acts directly as a carcinogen, it may act as a promoter. Rats which inhaled 4 – 10 ppm sulfur dioxide (1-6 H/day, 5 days/week) and were intermittently exposed to benzo[a]pyrene (B[a]P) had a substantial increase in respiratory tract squamous cell carcinomas when compared to exposures to B[a]P or SO₂ alone.

Mutagenic:

Genetic changes observed in mammalian, insect bacterial and yeast cell assay systems. Sulfur dioxide has failed consistently to induce gene toxicity in intact rodents.

Reproductive:

Experimental inhalation exposures of rats and mice at 1.5 to 32 ppm resulted in toxicity to both the male and female reproductive systems. Effects included menstrual cycle changes and toxic effects to testes. Developmental abnormalities were observed in newborn of exposed pregnant animals.

Ecological Information

Environmental Fate:

The average residence time of pollution sulfur is generally between one and five days depending on the climate of a region. Spring melts of accumulated winter snow packs may result in rapid short-term inputs of high sulfate, low pH water to freshwater systems with disastrous effects on fish.

This product does not contain any class 1 or class 2 ozone depleting substances.

Disposal Considerations

Do not attempt to dispose of waste or unused quantities in returnable cylinders. Return in the shipping container, *properly labeled, with any valve outlet plugs or caps secure and valve protection cap in place* to NorLab for proper disposal. Non-refillable containers should be vented in a well-ventilated area then disposed of in compliance with local regulations, or returned to NorLab.

Transportation Information

Parameter	United States DOT	Canada TDG
Proper Shipping Name:	Compressed gas, N. O. S., (sulfur dioxide, nitrogen)	Compressed gases, N. O. S.
Hazard Class:	2.2	2.2
Identification Number:	UN 1956	UN 1956
Shipping Label:	Non Flammable Gas	Non Flammable Gas

Regulatory Information

Sulfur dioxide is listed under the accident prevention provisions of section 112 (r) of the Clean Air Act (CAA) with a threshold quantity (TQ) of 5,000 pounds.

SARA Title III Notifications and Information:

Sulfur dioxide is listed as an extremely hazardous substance (EHS) subject to state and local reporting under Section 304 of SARA Title III (EPCRA). The presence of sulfur dioxide in quantities in excess of the threshold planning quantity (TPQ) of 500 pounds requires certain emergency planning activities to be conducted.

SARA Title III – Hazard Classes:

- Acute Health Hazard
- Chronic Health Hazard
- Sudden Release of Pressure Hazard

California Proposition 65: This product does not contain ingredient(s) know to the State of California to cause cancer or reproductive toxicity.

Other Information

Compressed gas cylinders must not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

Disclaimer of expressed and implied warranties:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user’s intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).



Emergency Contact: Chemtrec (800) 424-9300
Or Norco (208) 336-1643

1125 West Amity Road
Boise, ID 83705
(208) 336-1643

Carbon Monoxide in Nitrogen 0.0001% to 20.0%

MATERIAL SAFETY DATA SHEET

Identification

Product Name: Carbon Monoxide in Nitrogen 0.0001% to 20.0%
Chemical Name: Carbon Monoxide in Nitrogen
Chemical Family: Gas Mixture
CAS Number: N/A
Common Names/Synonyms: N/A
MSDS Identification Code/Number: 2070
Prepared by: Quality Dept.

Revision Date: 05-01-03
Last Review Date: 03/04/13

Composition, Information on Ingredients

Exposure Limits¹

Ingredient	% Volume	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Nitrogen Formula: N ₂ CAS Number: 7727-37-9 RTECS #: QW9700000	80.0 to 99.9999	None Established	Simple Asphyxiant	Not Available
Carbon Monoxide Formula: CO CAS Number: 630-08-0 RTECS#: FG3500000	0.0001 to 20.0	50 PPM TWA 25 PPM Canada	25 PPM TWA	LC 50 3760 PPM RAT Time Adj.

¹ Refer to individual state or provincial regulations, as applicable, for limits which may be more stringent than those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

³ As stated in the ACGIH 2007 Threshold Limit Values for Chemical Substances and Physical Agents

Hazard Identification

Emergency Overview:

Non-flammable, colorless, odorless gas. Nitrogen acts as a simple asphyxiant, displacing atmospheric oxygen and may cause asphyxiation if released in a confined area. Carbon monoxide acts as a chemical asphyxiant, binding to the blood hemoglobin, greatly reducing the red blood cell's ability to transport oxygen to body tissues. Effects may include headaches, dizziness, convulsions, loss of consciousness and death. Contents under pressure. Use and store below 125⁰F (52⁰C).

Route of Entry:

Skin Contact No	Skin Absorption No	Eye Contact No	Inhalation Yes	Ingestion No
--------------------	-----------------------	-------------------	-------------------	-----------------

Health Effects:

Exposure Limits Yes	Irritant No	Sensitization No
Teratogen Yes	Reproductive Hazard Yes	Mutagen Yes
Synergistic Effects None reported		

Hazards Identification Continued

Carcinogenicity: NTP: No IARC: No OSHA: No

Eye Effects:

Contact with rapidly expanding gas near the point of release may cause frostbite.

Skin Effects:

Contact with rapidly expanding gas near the point of release may cause frostbite with redness, skin color change to gray or white, and blistering.

Ingestion Effects:

None known. Ingestion is unlikely.

Inhalation Effects:

Depending on the concentration of the carbon monoxide present, this product may act as a simple asphyxiant or a chemical asphyxiant.

Inhaled carbon monoxide binds with blood hemoglobin to form carboxyhemoglobin. Carboxyhemoglobin can not take part in normal oxygen transport, greatly reducing the blood's ability to transport oxygen. Depending on levels and duration of exposure, symptoms may include headache, dizziness, heart palpitations, weakness, confusion, nausea, and even convulsions, eventual unconsciousness and death.

Some experimental evidence indicates teratogenic and reproductive effects.

Medical Conditions Aggravated by Exposure:

Recovery from carbon monoxide may be adversely affected by obesity, alcoholism, and chronic heart disease.

NFPA Hazard Codes

Health: 1
 Flammability: 0
 Instability: 0

HMIS Hazard Codes

Health: 1
 Flammability: 0
 Physical Hazard: 3

Ratings System

0 = No Hazard
 1 = Slight Hazard
 2 = Moderate Hazard
 3 = Serious Hazard
 4 = Severe Hazard

Hazard Data from: *CGA P-19-2004, CGA Recommended Hazard Ratings for Compressed Gases, Second edition*

First Aid Measures

Eyes:

Never introduce ointment or oil into the eyes without medical advice! Remove victim from the source of contamination. Flush eyes with water for 15 minutes. If pain is present, refer the victim to an ophthalmologist for treatment and follow up. If the victim cannot tolerate light, protect the eyes with a light bandage. If frostbite is suspected, flush with cool water for 15 minutes and obtain immediate medical attention.

Skin:

None required for gas. For frostbite, immerse skin in lukewarm water. DO NOT USE HOT WATER. Obtain medical attention.

Ingestion:

None required.

Inhalation:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO THIS PRODUCT. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Conscious persons should be assisted to an uncontaminated area and be treated with supplemental oxygen. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area and be given artificial respiration and oxygen at the same time. Administration of 100% oxygen by tight fitting face mask reduces the biological half-life of CO.

First Aid Measures Continued

FOR SEVERELY POISONED PATIENTS, HYPERBARIC OXYGEN THERAPY SHOULD BE CONSIDERED. The administering of the oxygen at an elevated pressure (up to 2 to 2.5 atmospheres) has shown to be beneficial as has treatment in a hyperbaric chamber. The physician should be informed that the patient has inhaled toxic quantities of carbon monoxide.

Fire Fighting Measures

Conditions of Flammability: Nonflammable		
Flash point: Not Available	Method: Not Available	Autoignition Temperature: Not Available
LEL(%): 12.5 (CO)		UEL(%) 74.0 (CO)
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: Not Available		

Fire and Explosion Hazards:

Non-flammable. Concentrations of carbon monoxide less than or equal to 20% in nitrogen are considered non-flammable (CGA P-23, 1995).

Extinguishing Media:

None required. Use media appropriate for surrounding materials.

Fire Fighting Instructions:

Firefighters should wear respiratory protection (SCBA) and full turnout or Bunker gear. If possible, stop the flow of gas supply. Use water spray to cool adjacent cylinders and areas.

Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest Norco/NorLab location.

Handling and Storage

Carbon monoxide can be handled in all commonly used metals up to approximately 500 psig (3450 kPa). Above that pressure it forms toxic and corrosive carbonyl compounds with some metals. Carbon steels, aluminum alloys, copper and copper alloys, low carbon stainless steels and nickel-based alloys such as Hastelloy A, B & C are recommended for higher pressure applications.

Use only in well-ventilated areas. Valve protection caps must remain in place unless the cylinder is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure (< 3000 psig) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

Protect cylinders from physical damage. Store in a cool, dry, well-ventilated area of non-combustible construction away from heavy traffic areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time.

For additional recommendations, consult Compressed Gas Association's Pamphlet P-1.

Exposure Controls, Personal Protection

Engineering Controls:

Hood with forced ventilation. Use local exhaust to prevent accumulation above the exposure limit. Use mechanical ventilation in accordance with electrical codes.

Exposure Controls, Personal Protection Continued

Eye/Face Protection:

Safety goggles or glasses as appropriate for the job.

Skin Protection:

Protective gloves made of any suitable material.

Respiratory Protection:

Positive pressure air line with mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

Other/General Protection:

Safety shoes.

Physical and Chemical Properties

Parameter	Value	Units
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Not Available	
Vapor density (Air = 1)	: Not Available	
Evaporation Point	: Not Available	
Boiling point	: Not Available	
Freezing point	: Not Available	
pH	: Not Available	
Specific gravity	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H ₂ O)	: Very slight	
Odor threshold	: Not Applicable	
Odor and appearance	: Odorless, colorless gas	

Stability and Reactivity

Stability:

Stable.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Carbon dioxide.

Hazardous Polymerization:

Will not occur.

Toxicological Information

Inhalation:

LC50: 3670 ppm inhalation/rat (Time Adj.).

Reproductive:

Inhalation of 150 ppm carbon monoxide for 24 hours by pregnant rats produced cardiovascular and behavioral defects in offspring. Toxic effects to fertility were observed in female rats exposed to 1 mg/m³ for 24 hours. Similar effects observed in other mammalian species.

Toxicological Information Continued

Mutagenic:

Genetic changes observed in mammalian cell assay systems at exposures of 1500 to 2500 ppm for 10 minutes.

Other:

Degenerative changes were observed in the brain of rats chronically exposed to 30 mg/m³ carbon monoxide.

Ecological Information

Product does not contain Class I or Class II ozone depleting substances. Not expected to bioconcentrate

Disposal Considerations

Do not attempt to dispose of waste or unused quantities in returnable cylinders. Return in the shipping container, *properly labeled, with any valve outlet plugs or caps secure and valve protection cap in place* to NorLab for proper disposal. Non-refillable containers should be vented in a well-ventilated area then disposed of in compliance with local regulations, or returned to NorLab.

Transport Information

Parameter	United States DOT	Canada TDG
Proper Shipping name:	Compressed gases, n.o.s., (Carbon Monoxide, Nitrogen)	Compressed gases, n.o.s.,
Hazard Class:	2.2	2.2
Identification Number:	UN 1956	UN 1956
Shipping Label:	Non-flammable Gas	Non-flammable Gas

Regulatory Information

SARA Title III Notification and Information:**SARA Title III – Section 313 Supplier Notification:**

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and CFR 372.

SARA Title III – Hazard Classes:

Acute Health hazard

Fire Hazard

Sudden Release of Pressure Hazard

California Proposition 65:

This product contains carbon monoxide, which the State of California has listed as having developmental toxicity.

Other Information

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

Disclaimer of Expressed and Implied Warranties:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).



Emergency Contact: Chemtrec (800) 424-9300
Or Norco (208) 336-1643

1125 West Amity Road
Boise, ID 83705
(208) 336-1643

Oxygen 5.0% to 23.5% in Nitrogen

MATERIAL SAFETY DATA SHEET

Identification

Product Name: Oxygen 5.0% to 23.5% in Nitrogen
Chemical Name: Oxygen in Nitrogen
Chemical Family: Gas Mixture
CAS Number: N/A
Common Names/Synonyms: N/A
MSDS Identification Code/Number: 2250
Prepared By: Quality Dept.

Revision Date: 11/02/06
Last Review Date: 04/10/13

Composition, Information on Ingredients, Exposure Limits

Exposure Limits¹

Ingredient	% Volume	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Oxygen Formula: O ₂ CAS: 7782-44-7 RTECS#: RS2060000	5.0 to 23.5	Not Available	Not Available	Not Available
Nitrogen Formula: N ₂ CAS: 7727-37-9 RTECS#: QW9700000	76.5 to 95	None Established	Simple Asphyxiant	Not Available

¹ Refer to individual state or provincial regulations, as applicable, for limits that may be more stringent than those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July1, 1993)

³ As stated in the ACGIH 2007 Threshold Limit Values for Chemical Substances and Physical Agents

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Hazards Identification

Emergency Overview:

Odorless, colorless nonflammable gas. Mixtures with less than 19.5% oxygen act as a simple asphyxiant. Effects may include headaches, dizziness and loss of consciousness. Non-toxic. Contents under pressure. Use and store below 125⁰F (52⁰C).

Route of Entry:

Skin Contact No	Skin Absorption No	Eye Contact No	Inhalation Yes	Ingestion No
--------------------	-----------------------	-------------------	-------------------	-----------------

Health Effects:

Exposure Limits No	Irritant No	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None known		

Hazards Identification Continued

Carcinogenicity: NTP: No IARC: No OSHA: No

Eye Effects:

Contact with rapidly expanding gas near the point of release may cause frostbite.

Skin Effects:

Contact with rapidly expanding gas near the point of release may cause frostbite with redness, skin color change to gray or white, and blistering.

Ingestion Effects:

None known. Ingestion is unlikely as product is a gas at room temperature.

Inhalation Effects:

Note: Not to be used as breathing air!

Mixtures which contain < 19.5% oxygen may act as simple asphyxiants. Effects of oxygen deficiency resulting from simple asphyxiants may include: rapid breathing, diminished mental alertness, impaired muscular coordination, faulty judgment, depression of all sensations, emotional instability, and fatigue. As asphyxiation progresses, nausea, vomiting, prostration, and loss of consciousness may result, eventually leading to convulsions, coma and death.

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

Medical Conditions Aggravated by Exposure:

None known.

NFPA Hazard Codes

Health: 0
Flammability: 0
Instability: 0

HMIS Hazard Codes

Health: 0
Flammability: 0
Physical Hazard: 3

Ratings System

0: No Hazard
1: Slight Hazard
2: Moderate Hazard
3: Serious Hazard
4: Severe Hazard

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, *CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition*.

First Aid Measures

Eyes:

None required for gas. If frostbite is suspected, flush eyes with cool water for 15 minutes and obtain immediate medical attention.

Skin:

None required for gas. For frostbite, immerse skin in lukewarm water. DO NOT USE HOT WATER. Obtain medical attention.

Ingestion:

None required.

Inhalation:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.

Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area and, if breathing has stopped, administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

Fire Fighting Measures

Conditions of Flammability: Not flammable		
Flash Point: None	Method: Not Applicable	Autoignition Temperature: None
LEL % None		UEL % None
Hazardous Combustion Products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

Fire and Explosion Hazards:

Nonflammable. Cylinder may rupture violently from pressure when involved in a fire situation.

Extinguishing Media:

None required. Use as appropriate for surrounding materials.

Fire Fighting Instructions:

If possible, stop the flow of gas supply. Use water spray to cool adjacent cylinders and areas. Fire fighters should wear a full-face piece NIOSH/MSHA approved self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout gear.

Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or valve, contact the appropriate emergency telephone number listed in section 1 or call your closest Norco/NorLab location.

Handling and Storage

Electrical classification:

Non-hazardous.

Do not use as breathing air.

Gas mixture is non-corrosive and may be used with all materials of construction. Moisture causes metal oxides which are formed with air to be hydrated so that they include volume and lose their protective role (rust formation). Concentrations of SO₂, Cl₂, salt, etc. in the moisture enhances the rusting of metals in air.

Use only in well-ventilated areas. Valve protection caps must remain in place unless the cylinder is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure (<3000 PSIG) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous backflow into the cylinder.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non-combustible construction away from heavy traffic areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in – first out" inventory system to prevent full cylinders from being stored for excessive periods of time

For additional recommendations, consult Compressed Gas Association Pamphlet P-1.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

Exposure Controls, Personal Protection

Engineering Controls:

Use local exhaust to prevent accumulation of high concentrations and maintain atmospheric oxygen at or above 19.5%.

Eye/Face Protection:

Safety goggles or glasses as appropriate for the job.

Exposure Controls, Personal Protection Continued

Skin Protection:

Protective gloves of material appropriate for the job.

Respiratory Protection:

Positive pressure air line with full-face mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

Other/General Protection:

Safety shoes.

Physical and Chemical Properties

Parameter	Value	Units
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Not Available	
Vapor density (Air = 1)	: 0.97	
Evaporation point	: Not Available	
Boiling point	: -320.4	°F
	: -195.8	°C
Freezing point	: -345.9	°F
	: -209.9	°C
pH	: Not Applicable	
Specific gravity	: 1	
Oil/water partition coefficient	: Not Available	
Solubility (H ₂ O)	: Slightly Soluble	
Odor threshold	: Not Applicable	
Odor and appearance	: Colorless, odorless gas	

Stability and Reactivity

Stability:

Stable

Incompatible Materials:

None

Hazardous Decomposition Products:

None

Hazardous Polymerization:

Does not occur.

Toxicological Information

Inhalation:

These mixtures of oxygen and nitrogen are not intended for breathing use since the oxygen concentration in the mixture may be below that which supports life. Oxygen levels should be maintained at greater than 19.5% at normal atmospheric pressure which is equivalent to a partial pressure of 135 mm Hg.

High concentrations of Nitrogen and low concentrations of oxygen in these gas mixtures may exclude adequate supply of oxygen to the lungs which causes dizziness, deeper breathing due to air hunger, possible nausea and eventual unconsciousness.

Toxicological Information Continued

Mixtures with less than 19.5% oxygen are relatively inactive biologically and essentially nontoxic. The major hazard is the exclusion of an adequate supply of oxygen to the lungs.

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

No data given in the Registry of Toxic Effects of Chemical Substances (RTECS or Sax, Dangerous Properties of Industrial Materials, 7th ed.

Reproductive:

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

Ecological Information

Product does not contain Class I or Class II ozone depleting substances. Not toxic. Will not bioconcentrate.

Disposal Considerations

Do not attempt to dispose of waste or unused quantities in returnable cylinders. Return in the shipping container, properly labeled, with any valve outlet plugs or caps secure and valve protection cap in place, to Norco or NorLab for proper disposal. Non-refillable containers should be vented in a well-ventilated area then disposed of in accordance with local regulations, or returned to NorLab.

Transport Information

Parameter	United States DOT	Canada TDG
Proper Shipping Name:	Compressed gas, N.O.S., (Oxygen, Nitrogen)	Compressed gases, N.O. S.,
Hazard Class:	2.2	2.2
Identification Number:	UN 1956	UN 1956
Shipping Label:	Nonflammable Gas	Nonflammable Gas

Regulatory Information

SARA Title III Notifications and Information:

SARA Title III- Section 313 Supplier Notification

This product does not contain any ingredients which are regulated on the U.S. EPA List of Toxic Chemicals (40 CFR 372), and is therefore no subject to release reporting under Section 313 of EPCRA/SARA Title III.

SARA Title III – Hazard Classes:

Sudden Release of Pressure Hazard

Acute Health Hazard

California Proposition 65: This product does not contain any ingredient(s) known to the State of California that cause cancer or reproductive toxicity.

Other Information

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

Disclaimer of Expressed and Implied Warranties:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).